

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **PEROXAN BD-Paste 50 SI**
- CAS Number: 133-14-2
- EC number: 205-094-9
- Registration number: 01-2119965137-32

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Reaction initiator
For industrial use

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50

Further information obtainable from:

Environment protection / Security of labour

Competent person:

* Sales Manager Germany: Mr. Ansgar Pappenheim, e-mail: a.pappenheim@pergan.com

* Export Sales Manager: Mr. Dr. Thomas Philipps, e-mail: dr.philipps@pergan.com

* Environment protection / : Mr. Christoph Wiltung, e-mail: c.wiltung@pergan.com

Security of labour

1.4 Emergency telephone number:

- Tel: +49 2871 9902-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Org. Perox. D H242 Heating may cause a fire.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360 May damage fertility or the unborn child.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The substance is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS08

Signal word

Danger

- Hazard-determining components of labelling:
- Hazard statements

di-2,4-dichlorobenzoyl peroxide
H242 Heating may cause a fire.
H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
P234 Keep only in original container.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P405 Store locked up.
P410 Protect from sunlight.
P411+P235 Store at temperatures not exceeding +30°C. Keep cool.
P420 Do not mix with peroxide-accelerators or reducing agents.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Restricted to professional users.

2.3 Other hazards

Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

Trade name: **PEROXAN BD-Paste 50 SI**

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.1 Chemical characterisation: Substances

- CAS No. Description 133-14-2 di-2,4-dichlorobenzoyl peroxide
- Identification number(s)
- EC number: 205-094-9
- Additional information: Bis(2,4-dichlorobenzoyl) peroxide 50%ig in Siloxanes and Silicone, dimethyl

Impurities and stabilising additives:

CAS: 63148-62-9	Siloxanes and Silicones, dimethyl
Polymer	

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:



Take care of personal protection for the first aider.

After inhalation:

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.
Immediately remove contaminated clothing.

After eye contact:

Rinse opened eye for several minutes under running water.

After swallowing:

If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.
Hydrocarbons, carbon dioxide and -monoxid.
polychlorinated biphenyls
furan
1,3-dichlorobenzene
2,4-dichlorobenzoic acid

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.
Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.
In case of further temperature should be cooled with waterspray from a safe distance.
Wear breathing apparatus with filter A during decomposition of materials.
Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:



Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Large quantities should be diluted with suitable desensitisation agent to a concentration below 10 % before disposal.
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 3)

Trade name: **PEROXAN BD-Paste 50 SI**

(Contd. of page 2)

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.
Store in cool, dry place in tightly closed receptacles.
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Do not refill residue into storage receptacles.
Restrict the quantity stored at the work place.
Use only in well ventilated areas.
Before break and at the end of work hands should be thoroughly washed.
Only use tools made of suitable materials (e. g. polyethylene or stainless steel).
Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
Oxidizing because of releasing oxygene.
Avoid contact with skin and eyes.
While using do not eat, drink or smoke.
Avoid shock and friction.

· Information about fire - and explosion protection:

Protect from heat.
Prevent impact and friction.
Keep respiratory protective device available.
Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

· 7.2 Conditions for safe storage, including any incompatibilities

· **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.

· Requirements to be met by storerooms and receptacles:

Store in a cool location.
Store only in the original receptacle.
Prevent any seepage into the ground.
Use only receptacles specifically permitted for this substance/product.

· Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.
Store away from foodstuffs, drinks and feeding stuffs.

· Further information about storage conditions:

Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
Protect from contamination.
Store under lock and key and out of the reach of children.
Store in a cool place.

· Recommended storage temperature (To maintain quality):

+5 +30 °C

· Storage class:

5.2

· 7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities:

No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

Not required.

· DNELs

133-14-2 di-2,4-dichlorobenzoyl peroxide

Dermal	DNEL Longterm System	10 mg/kg bw/day (Worker)
--------	----------------------	--------------------------

(Contd. on page 4)

Trade name: PEROXAN BD-Paste 50 SI

(Contd. of page 3)

Inhalative	DNEL Longterm System	3.53 mg/m3 (Worker)
· PNECs		
133-14-2 di-2,4-dichlorobenzoyl peroxide		
PNEC Marinewater sed	0.38 mg/kg sed dw	
PNEC Freshwater	0.0006 mg/l (AF 50)	
PNEC Freshwater sed	3.8 mg/kg sed dw	
PNEC Soil	0.76 mg/kg soil dw	
PNEC STP	50 mg/l (AF 10)	
PNEC Marinewater	0.00006 mg/l (AF 500)	
· Additional information: The lists valid during the making were used as basis.		
· 8.2 Exposure controls		
· Personal protective equipment:		
· General protective and hygienic measures:		
The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid close or long term contact with the skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Be sure to clean skin thoroughly after work and before breaks.		
· Respiratory protection:		
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.		
		
Filter A2		
· Protection of hands:		
Only use chemical-protective gloves with CE-labelling of category III.		
		
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation		
Protective gloves		
· Material of gloves		
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene		
· Penetration time of glove material		
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.		
· Eye protection:		
		
Tightly sealed goggles		
· Body protection:		
		
Protective work clothing		

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Appearance:	
· Form:	Pasty
· Colour:	white - yellowish
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
· Melting point/Melting range:	Not applicable.
· Boiling point/Boiling range:	Not applicable.
· Flash point:	Not determined.
· Flammability (solid, gaseous):	Not applicable.

(Contd. on page 5)
GB

Trade name: **PEROXAN BD-Paste 50 SI**

(Contd. of page 4)

· Decomposition temperature:	+60 °C (SADT)
· Self-igniting:	Not determined.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.2 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· water:	Undetermined.
· Partition coefficient (n-octanol/water):	not determined
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.
· Active oxygen	2.1 - 2.2 %

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT. No decomposition if used and stored according to specifications. To avoid thermal decomposition do not overheat.
· 10.3 Possibility of hazardous reactions	Self-accelerating decomposition at SADT.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
· 10.6 Hazardous decomposition products:	Hydrocarbons, carbon dioxide and -monoxid. polychlorinated biphenyls furan 1,3-dichlorobenzene 2,4-dichlorobenzoic acid No hazardous decomposition products if used and stored according to specifications.
· Additional information:	Emergency procedures will vary depending on conditions. The customer should have an emergency response plan in place.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

133-14-2 di-2,4-dichlorobenzoyl peroxide

Oral	LD50	>12000 mg/kg (rattus male)
		>2500 mg/kg (rattus female)
Dermal	LD50	>8000 mg/kg (cuniculus)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 6)
GB

Trade name: **PEROXAN BD-Paste 50 SI**

(Contd. of page 5)

- | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> · Carcinogenicity · Reproductive toxicity · STOT-single exposure · STOT-repeated exposure · Aspiration hazard | <p>Based on available data, the classification criteria are not met.</p> <p>May damage fertility or the unborn child.</p> <p>Based on available data, the classification criteria are not met.</p> <p>Based on available data, the classification criteria are not met.</p> <p>Based on available data, the classification criteria are not met.</p> |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

133-14-2 di-2,4-dichlorobenzoyl peroxide

LC50 / 96h >1000 mg/l (poecilia reticulata)

EC50 / 48h >100 mg/l (daphnia magna)

· 12.2 Persistence and degradability

No further relevant information available.

· 12.3 Bioaccumulative potential

No further relevant information available.

· 12.4 Mobility in soil

No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment

· PBT:

Not applicable.

· vPvB:

Not applicable.

· 12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste disposal key:

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.

· Uncleaned packaging:

· Recommendation:

This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA

UN3106

· 14.2 UN proper shipping name

· ADR

3106 ORGANIC PEROXIDE TYPE D, SOLID (DI-2,4-DICHLOROBENZOYL PEROXIDE)

· IMDG, IATA

ORGANIC PEROXIDE TYPE D, SOLID (DI-2,4-DICHLOROBENZOYL PEROXIDE)

· 14.3 Transport hazard class(es)

· ADR



· Class

5.2 (P1) Organic peroxides.

· Label

5.2

· IMDG, IATA



· Class

5.2 Organic peroxides.

· Label

5.2

(Contd. on page 7)

GB

Trade name: **PEROXAN BD-Paste 50 SI**

(Contd. of page 6)

· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user · Danger code (Kemler): · Stowage Category · Stowage Code · Segregation Code	Warning: Organic peroxides. - D SW1 Protected from sources of heat. SG35 Stow "separated from" acids. SG36 Stow "separated from" alkalis.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	500 g Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
· RID / GGVSEB:	like ADR
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	500 g Code: E0 Not permitted as Excepted Quantity

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Directive 2012/18/EU
 - Named dangerous substances
 - ANNEX I Substance is not listed.
 - Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES
 - Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
 - Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
 - REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
 - National regulations:
 - Other regulations, limitations and prohibitive regulations
 - Please note: Take care of the respective local regulations.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Environment protection / Security of labour
- Contact: Tel: +49 2871 9902-0
E-mail: mail@pergan.com
- Abbreviations and acronyms:
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Org. Perox. D: Organic peroxides – Type C/D
 - Skin Sens. 1: Skin sensitisation – Category 1
 - Repr. 1B: Reproductive toxicity – Category 1B